

Self-Storing Rear Walkramp for use with the Demountable Hydraulic "Swap-Body" System

Patented (#7,819,619)



No more struggling

This ramp slides in and out of the chassis lift for quicker, safer deliveries

- High quality R.O.M. walkramp - *recognized industry-wide for safety and durability*
- Industry proven monorail track ensures that ramp slides smoothly
- Constructed of strong yet lightweight aluminum frame and magnesium castings
- Aggressive traction surface and open castings for added driver safety
- Available on all new Demountable orders



Ramp self-stores inside of Demountable chassis lift



Can be set up and stored quickly and easily by one person



DEMOUNTABLE CONCEPTS, INC.

Toll Free 1-800-254-3643

Self-Storing Rear Walk Ramp Features

- Easy-to-Handle
- Maintenance Free
- Strong & Durable



Ramp stores in chassis lift for convenience



Standard lift assist reduces driver fatigue



Strong monorail track with heavy duty support brackets



Aggressive traction surface enhances safety



Open castings prevent build-up of slippery materials



Easy to attach to truck body in correct position



Smooth transitions on and off ramp



Integrated handles make set-up quick and easy




Spring loaded latch holds ramp securely in place

Also features bolted modular construction (no welds) for easy field repairs and a reversible double-sided walk surface that virtually doubles product life

Nominal Length	Ramp Height	Usable Width	Outer Ramp Width	Recommended Deck Height	Part Number
10 ft.	3-3/4"	20-1/2"	22-5/16"	31" to 38"	DCWR-10
12 ft.	3-3/4"	20-1/2"	22-5/16"	39" to 46"	DCWR-12
14 ft.	3-3/4"	20-1/2"	22-5/16"	47" to 56"	DCWR-14
16 ft.	3-3/4"	20-1/2"	22-5/16"	57" to 64"	DCWR-16

Patented (#7,819,619)



DEMOUNTABLE CONCEPTS, INC.

200 Acorn Road, Glassboro, NJ 08028

Toll Free 1-800-254-3643

www.demount.com sales@demount.com