



DEMOUNTABLE CONCEPTS, INC.

**Getting Your Trucks On The Road
Faster And More Efficiently.**

800-254-3643

Semi-Trailer Specifications

Trailer Length

- 22'- 53': designed to carry two, three or four demountable bodies

Locking System

- individual locking assemblies for each body
- four (4) over center locking hooks to match
- each body locking dimensions

Electrical

- two (2) flood lights mounted at front of trailer
- MAIN RAILS
- 18" twin I-beam on 34" centers

Tires

- 11 R 22.5 - made in USA

Body Spacing

- 3" thick steel tapered body dividers to maintain spacing between bodies

Axles

- 5/8" wall - 5" round axle
- 22,000 pound individual capacity

Gooseneck

- 6 1/2" gooseneck with 36" king pin setting

Suspension

- tandem air-ride per customer requirements

Safety Devices

- spring loaded body locking pins
- pad-lockable safety key

Wheels

- 10 hole hub piloted steel disc wheels with outboard drums

Lift Gear

- Air controls, regulator, pressure gauge in weather tight box. Utilize trailer and tractor air suspension for lifting

Other Standard Features

- 16 1/2 x 7 s-cam brakes with automatic slack adjusters
- all required air connectors for tractor connection
- trussing reinforcement in trailer transition area
- one (1) additional air tanks to supply air to lifting gear
- 7-way ATA electrical receptacle for tractor to trailer connection
- two (2) four-way light plugs to power TruckTainer body lights
- DOT approved ICC/Under ride guard/bumper
- 1/4" mud flaps with spring loaded mud flap brackets
- DOT approved red and white reflective tape on trailer
- sides and rear

Finish

- black